

STEYR AUG A3



The STEYR AUG A3 modular weapon system is the latest result of the continued development of the world renowned STEYR AUG rifle series. The STEYR AUG A3 design is also based on modular system components, which can be configured from one variant to another quickly and easily, without tools, and at unit level, in order to meet a wide range of future weapon requirements.

The "Bull Pup" design maintained its short overall length, without influencing the barrel length, to meet or exceed required accuracy standards. The STEYR AUG A3 features a number of Picatinny rails (Mil. Std. 1913 rails), which allow the quick and easy mounting of various accessories, such as illumination and target acquisition devices, including a variety of optics or night vision devices.

Due to its utmost flexibility design concept, the STEYR AUG A3 is a state-of-the-art, multipurpose assault rifle, for day and night operations. Armed and special forces in about 35 countries in the whole world are trusting in the STEYR AUG.

STEYR AUG A3

SPECIFICATIONS

Caliber	5,56x45 mm
Rate of fire	Automatic fire: 680-750 rounds per min.
Barrel groups	Interchangeable, 365 mm (14,5"), 407 mm (16"), 455 mm (18"), 508 mm (20") with gas regulator. Cold hammer forged, chrome-lined bore including chamber. Bottom integrated Picatinny rail.* Left side mounted rail.
Weight empty	With 455 mm (18") barrel: 3,9 kg
Overall length	With 455 mm (18") barrel: 745 mm
Overall height	245 mm
Magazine	Detachable, synthetic (transparent) staggered box type.
Magazine weight	0,13 kg
Magazine capacity	30 rounds, 42 rounds (optional)
Action	Gas-operated. Gas regulator with two action settings for firing, to guarantee proper function under all conditions.
Trigger	"Pull through" trigger system. Fires semi automatic when pulled halfway to a clearly felt point, fires fully automatic when pulled fully back.
Trigger mechanism	Synthetic (except for springs, steel bearing pins and catch holding open). Option 3 rounds burst.
Safety	Lateral push-through type locks trigger.
Housing group	Mil. Std. 1913 flat top rail with attached optical sight 1.5x magnification and ring reticule, short rail side mounted.
Stock	Synthetic, olive-drab or black. External bolt release.
Bolt	Fixed locking turn bolt, with seven locking lugs. The rifle can be changed easily from right to left hand ejection, simply by flipping the ejection port lid to the other side and installing a left hand bolt (no tools required).



STEYR AUG A3